

# HEX REDUCER (HR)

## Model Selection Chart

Sr. No.	End Conn 1 Thread type NPT Male	End Conn 2 Thread type NPT Female	Model No. For MOC: SS316
1	1/4"	1/8"	SS-HR-4M-2F
2	3/8"	1/8"	SS-HR-6M-2F
3	3/8"	1/4"	SS-HR-6M-4F
4	1/2"	1/8"	SS-HR-8M-2F
5	1/2"	1/4"	SS-HR-8M-4F
6	1/2"	3/8"	SS-HR-8M-6F
7	3/4"	1/4"	SS-HR-12M-4F
8	3/4"	3/8"	SS-HR-12M-6F
9	3/4"	1/2"	SS-HR-12M-8F
10	1"	1/2"	SS-HR-16M-8F
11	1"	3/4"	SS-HR-16M-12F
12	1-1/4"	1"	SS-HR-20M-16F
13	1-1/2"	1"	SS-HR-24M-16F
14	1-1/2"	1-1/4"	SS-HR-24M-20F
15	2"	1"	SS-HR-32M-16F
16	2"	1-1/2"	SS-HR-32M-20F



### Material Grade Selection Chart

For following Material Grade (MOC)	Replace First Two Letters of Model No. with following
SS316L	SSL
SS304	S4
SS304L	S4L
Brass	B
Alloy 400	ML
Alloy 600	INC
Alloy C276	HC
PTFE	T
Carbon Steel	CS

Note: Above Model Nos. are for NPT Threads. For BSP Threads Add -B & for BSPT Threads add -BT at end of Each Size in Model Nos.

Hex Adaptor shall be supplied with our standard short Length.

For Specific Length required for Hex Adaptor, add -Length in mm at the end of the Model No.

Head Office

"TRUEWAY HOUSE", Plot No. 535/14-15, Sonawala Cross Road No. 2, Nr. M.K. Industrial Estate, Goregaon ( East ),  
Mumbai - 400 063, INDIA. Mobile : +91 9321756212, +91 9004146034 | Phone : +91 22 26852241, 26851052.

E-mail

sales@truesdayindia.in

Website

www.truesdayindia.in

TRUEWAY ENGINEERING INDUSTRIES

An ISO 9001 : 2015 Certified Company