

Non Return Valve (NRV)

Model Selection Chart

| | NPT (Female) x NPT (Female) | | |
|---------|---------------------------------|-------------------------------|-------------------------------------------|
| Sr. No. | Inlet Thread Type NPT Female | Outlet Thread type NPT Female | Model No. For MOC: SS316 |
| 1 | 1/4" | 1/4" | SS-NRV-4F |
| 2 | 3/8" | 3/8" | SS-NRV-6F |
| 3 | 1/2" | 1/2" | SS-NRV-8F |
| 4 | 3/4" | 3/4" | SS-NRV-12F |
| 5 | 1" | 1" | SS-NRV-16F |

| NPT (Female) x NPT (Female) | | | |
|-----------------------------|---------------------------------|-------------------------------|-------------------------------------------|
| Sr. No. | Inlet Thread Type NPT Female | Outlet Thread type NPT Female | Model No. For MOC: SS316 |
| 1 | 1/4" | 1/4" | SS-NRV-4F |
| 2 | 3/8" | 3/8" | SS-NRV-6F |
| 3 | 1/2" | 1/2" | SS-NRV-8F |
| 4 | 3/4" | 3/4" | SS-NRV-12F |
| 5 | 1" | 1" | SS-NRV-16F |

| NPT (Male) x NPT (Female) | | | |
|---------------------------|-------------------------------|----------------------------------|-------------------------------------------|
| Sr. No. | Inlet Thread Type NPT Male | Outlet Thread type NPT Female | Model No. For MOC: SS316 |
| 1 | 1/4" | 1/4" | SS-NRV-4M-4F |
| 2 | 3/8" | 3/8" | SS-NRV-6M-6F |
| 3 | 1/2" | 1/2" | SS-NRV-8M-8F |
| 4 | 3/4" | 3/4" | SS-NRV-12M-12F |
| 5 | 1" | 1" | SS-NRV-16M-16F |

| | Tube OD x Tube OD, Tube OD Dia Size: Fractional | | |
|---------|-------------------------------------------------|------------------------------|-------------------------------------------|
| Sr. No. | Inlet Tube OD Size: Inch | Outlet Tube OD Size: Inch | Model No. For MOC: SS316 |
| 1 | 1/4" | 1/4" | SS-NRV-4 |
| 2 | 1/2" | 1/2" | SS-NRV-8 |

| | Tube OD x Tube OD, Tube OD Dia Size: Metric | | | |
|---------|---------------------------------------------|----------------------------|-------------------------------------------|--|
| Sr. No. | Inlet Tube OD Size: MM | Outlet Tube OD Size: MM | Model No. For MOC: SS316 | |
| 1 | 6mm | 6mm | SS-NRV-6mm | |
| 2 | 12mm | 12mm | SS-NRV-12mm | |



| Material Grade Selection Chart | | | |
|--------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|--|--|
| For following Material Grade (MOC) | Replace First Two Letters of Model No. with following | | |
| SS316L | SSL | | |
| SS304 | S4 | | |
| SS304L | S4L | | |
| Brass | В | | |
| Alloy 400 | ML | | |
| Alloy 600 | INC | | |
| Alloy C276 | HC | | |
| Carbon Steel | CS | | |
| Note: Above Model Nos, are for NPT Threads, For BSP Threads Add -B & for BSPT Threads add -BT at end of Model Nos, | | | |

Head Office

"TRUEWAY HOUSE", Plot No. 535/14-15, Sonawala Cross Road No. 2, Nr. M.K. Industrial Estate, Goregaon (East), Mumbai - 400 063, INDIA. Mobile: +91 9321756212, +91 9004146034 | Phone: +91 22 26852241, 26851052.

sales@truewayindia.com E-mail

Website

www.truewayindia.com

